

Solis-3P(5-10)K-4G-LV

Solis Three Phase Inverters



360 degree

Features:

- ▶ Max. efficiency 98%
- ▶ Wide voltage range and low startup voltage
- ▶ 2 MPPT design with precise MPPT algorithm
- ▶ THDi<1.5%, low harmonic distortion against grid
- ▶ Multiple protections levels
- ▶ Intergrated Export Power Manager (EPM)



Model:

220V: Solis-3P5K-4G-LV Solis-3P6K-4G-LV
Solis-3P10K-4G-LV

Datasheet

Model Name	Solis-3P5K-4G-LV	Solis-3P6K-4G-LV	Solis-3P10K-4G-LV
Input DC			
Recommended max. PV power	6 kW	7.2 kW	12 kW
Max. input voltage	1000 V		
Rated voltage	330 V		
Start-up voltage	180 V		
MPPT voltage range	160-500 V		
Max. input current	11 A / 11 A		22 A / 22 A
Max. short circuit current	17.2 A / 17.2 A		34.3 A / 34.3 A
MPPT number/Max. input strings number	2/2		2/4
Output AC			
Rated output power	5 kW	6 kW	10 kW
Max. apparent output power	5.5 kVA	6.6 kVA	11 kVA
Max. output power	5.5 kW	6.6 kW	11 kW
Rated grid voltage	3/PE, 208 V / 220 V / 240 V		
Rated grid frequency	50 Hz / 60 Hz		
Rated grid output current	13.1 A	15.7 A	26.2 A
Max. output current	14.4 A	16.7 A	28.8 A
Power Factor	>0.99 (0.8 leading - 0.8 lagging)		
THDi	<1.5%		
Efficiency			
Max. efficiency	98.0%		
EU efficiency	97.5%		
Protection			
DC reverse-polarity protection	Yes		
Short circuit protection	Yes		
Output over current protection	Yes		
Surge protection	Yes		
Grid monitoring	Yes		
Anti-islanding protection	Yes		
Temperature protection	Yes		
Integrated AFCI (DC arc-fault circuit protection)	Yes*		
Integrated DC switch	Optional		
General Data			
Dimensions (W*H*D)	310*563*219 mm		
Weight	18 kg	19.8 kg	
Topology	Transformerless		
Self consumption (night)	<1 W		
Operating ambient temperature range	-25 ~ +60°C		
Relative humidity	0-100%		
Ingress protection	IP65		
Cooling concept	Natural convection	Intelligent redundant fan-cooling	
Max. operation altitude	4000 m		
Grid connection standard	G98 or G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1, VDE 0126 / UTE C 15 / VFR:2019, RD 1699 / RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530		
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4		
Features			
DC connection	MC4 connector		
AC connection	Quick connection plug		
Display	LCD		
Communication	RS485, Optional: Wi-Fi, GPRS		

* Activation required.